CIAIA	85-10062JX

Top Secret

25X1

25X1

IL-76 Candid: Status and **Outlook for the Soviets' Major Transport Aircraft Program**

A Research Paper

NOT MICROFILMED Color Copes For Data Entry Only

NGA Review Completed

Top Secret

December 1985

IA 85-10062JX



IL-76 Candid: Status and Outlook for the Soviets' Major Transport Aircraft Program

25X1

A Research Paper

25X1

The authors of this report are

25X1

25X1

Office of Soviet Analysis, and Office of Scientific and Weapons Re-

25X1

search, contributed to this report.

25X1

Comments and queries are welcome and may be

25X1

directed to the

25X1

Top Secret IA 85-10062JX 25X1

December 1985

Sanitized Copy Approved	for Release 2009/11/09 : CIA-RDP90T01298R000300250001-4	
	Top Secret	
•	25	X 1
	IL-76 Candid: Status and Outlook for the Soviets' Major Transport Aircraft Program	25X1
Summary Information available as of 1 December 1985 was used in this report.	The Soviet IL-76 transport aircraft—codenamed Candid by NATO—forms the backbone of the Soviets' military air transport assets and will continue to do so into the next century. It is similar in mission and design to the US C-141, but can carry a greater payload, although to a lesser range.	25X1
		25 X 1
	The IL-76s assigned to the military are replacing the older and less capable AN-12 aircraft in Soviet Military Transportation Aviation, the Soviet equivalent of the US Military Airlift Command. By 1992, we project that all military AN-12s will have been replaced by IL-76s, providing Soviet Military Transport Aviation with a fleet of some 440 of these aircraft. (By comparison, some 285 C-141s were produced for the US military.) The primary mission of the aircraft is to provide the airlift for Soviet airborne forces. Compared to the capabilities of an AN-12, an IL-76 can carry a greater variety of equipment, can carry over twice the weight, and can carry that weight twice as far at a third higher speed. These capabilities enable the Soviet airborne forces and their equipment to be delivered and resupplied, without refueling, to almost all of Europe, North Africa, and the Middle East. The IL-76 also increases the Soviets' ability to conduct massive airlifts to client states throughout the world.	25X1
25X1	AWACS variant and an in-flight refueling tanker vari-	
25 X 1	ant of the IL-76 began	25X1
25X1	cause of the growing Soviet need for these special-purpose aircraft, we estimate they will produce at least another 25 AWACS and 70 to 80 more tankers. The AWACS variant provides the Soviets with a sophisticated radar capable of tracking low-flying targets and directing Soviet fighters to intercept them. The AWACS is the only IL-76 with an in-flight refueling capability and will probably	
	,	

Top Secret

1A 85-10062JX

December 1985

iii

Sanitized	d Copy Approved for Release 2009/11/09 : CIA-RDP90T01298R000300250001-	-4
Top Secret		
25X1		
25X1	be refueled by IL-76 tankers. IL-76 tankers will probably be produced in sufficient numbers to support strategic bombers and tactical fighters as well. Based on our estimate of the Soviets' requirements for IL-76 aircraft, we believe they will probably produce 280 to 330 more aircraft, making a total production run of 750 to 800. The Soviet military will continue to receive most of these aircraft. We estimate current production to be 60 aircraft per year, and our analysis indicates that this figure is at or very near the peak of production. We expect this peak rate to be maintained for only a year or two longer before production begins to taper off. The decline will probably be caused by diminishing requirements for standard IL-76s, increasing production of the more complex AWACS and tanker variants, and the beginning of major component production for the new heavy transport aircraft, the AN-124. We estimate that about three to five AWACS and about six to eight tankers will be produced each year until Soviet requirements for these variants are satisfied. We expect that civil and export models, as well as additional variants, will also continue to be produced.	25X1 25X1 25X1
		20/(1
25X1		25X1
Top Secret	iv	

25 X ²

Contents

Special-Purpose IL-76s

	Page	
Summary	iii	
Introduction	1	
IL-76 Performance and Capability	1	
	5	25X1
	8	
Military Aircraft	8	
Civil (Aeroflot) Aircraft	11	
Export Aircraft	11	
IL-76 Variants	11	
AWACS	12	
Airborne Tanker	13	
Electronic Support	13	
Maintenance	15	
Assessment of Future Production	16	
		25X1
Appendix		
		_

25

25X1

Top Secret

₹·	Top Secret
Scope Note	This paper presents a comprehensive discussion of the Soviet IL-76
	Candid transport aircraft program. It describes the capabilities of this aircraft, discusses its primary role as a military transport, and addresses the more recent development of AWACS and in-flight refueling
25 X 1	variants.

25X1 vii Top Secret 25X1


	Sanitized Copy Approved for Release 2009/11/09	: CIA-RDP90T01298R000300250001-4	
		Top Secret	25X1
	IL-76 Candid: Status and Outlook for the Soviets' Major Transport Aircraft Program		25X1
	Introduction		
	As the Soviets rebuilt and expanded their economy and military forces in the decades following World War II, the need arose for larger and more capable transport aircraft. Transports were needed that would be large enough to carry construction equipment and supplies to growing communities and resource exploration sites in the Soviet Far		25X1
	East and Siberia, and to move Soviet airborne troops and their equipment to potential conflict		 25 X 1
	sites beyond the homeland borders. The inspira-	IL-76 Performance and Capability	
05)/4	tion for an aircraft to fulfill this role came during the early 1960s with the development of the US Lockheed C-141 Starlifter. This new US aircraft stimulated Soviet interest in a new transport, and	the initial design requirements for the IL-76 specified that the air-	25 X 1
25 X 1		craft be capable of transporting a 40-ton payload over 5,000 kilometers in not more than six and a	
25X1	The Soviet aircraft was similar in size and general appearance to the C-141 and incorporated many of its design features. Some features, however, were altered to conform to Soviet production capabilities or to better satisfy Soviet user requirements. Five prototype aircraft, designated IL-76 by the Soviets and Candid by NATO, were built between 1969 and late 1972. The first of	half hours. These requirements established the basic structural and fuel weights of the IL-76 and, in fact, were among the advertised performance characteristics given by the Soviets during the initial display of the aircraft at Paris in 1971. At that time the new director of the Ilyushin OKB, Genrikh Novozhilov, announced that the IL-76 was a military transport with a secondary role as a civil	25X1
25X1	these had its initial flight in late 1970 and was shown at the Paris Air Show in mid-1971.	bulk cargo carrier.	25X1
25 X 1	The Soviets have invested heavily in resources that appear dedicated to a long production run of the IL-76. Apparently the aircraft has performed satisfactorily and will probably fulfill most of the Soviets' military transport	The military IL-76 has a tail-gun turret Other differences between military and civil aircraft, however, are probably minimal. All IL-76s,	25X1 25X1 25X1
25.44	requirements and many civil requirements into the 21st century. Two variants of the IL-76, an AWACS and an in-flight refueling tanker, have only recently entered series production; it is unlikely that the military requirements for these aircraft will be satisfied until the early 1990s.	with the probable exception of AWACS variants, are equipped with an integral loading ramp and can load and unload cargo without much airfield support equipment. This capability and the undercarriage, designed for rough field use, enable both the military and civil IL-76 to use many of the unimproved airstrips found in remote areas of the	
25 X 1	25X1		
25 X 1	1	Top Secret 25X1	


Sanitized Copy Approved for Release 2009/11/09: CIA-RDP90T01298R000300250001-4 Top Secret 25X1 25X1 USSR and in the Third World. have reinforced cargo floors for heavy equipment and pressurized cargo compartments for transport of personnel or paratroops. 25X1 In appearance and size the IL-76 is much like its US counterpart, the C-141 (figure 1). While the Ilyushin Design Bureau obviously borrowed heavily from the Lockheed C-141, they did not simply copy it. The IL-76 fuselage diameter is greater than that of the C-141 to accommodate wider equipment; its landing gear is heavier for rough field use; and it can carry a larger payload, although to a lesser range. Table 2 lists the known characteristics and capacities of the IL-76 and 25X1 compares them with those of the C-141. 25X1 Candids initially were designated IL-76 and had a maximum takeoff weight of 157,000 kilograms. Later Candids—IL-76T and IL-76M—have maximum takeoff weights of 170,000 kilograms, with the weight increase due to a larger fuel capacity. The early IL-76s are now being retrofitted to have the 170,000-kilogram gross weight and increased fuel load. Within the last few years, two additional types of Candids have entered production—the IL-76TD and IL-76MD. These newer variants reportedly have an additional increase in fuel capacity and a heavier maximum takeoff weight of 190,000 kilograms. 25X1 The range and payload capabilities of the IL-76 25X1 are greatly superior to most Soviet cargo transport aircraft. Only the old AN-22 (Cock) and the newly designed AN-124 (Condor), not yet in production, can lift more cargo and carry it farther. There are more than six times as many IL-76s as there are AN-22s available for airlift operations. The IL-76 force is thus the primary vehicle for air transport and enables the Soviet airborne forces and their equipment to be delivered and resupplied to almost all of Europe, North Africa, and the Middle East. 25X1 25X1

Top Secret

2

Figure 1 Soviet IL-76 and US C-141 Transports





3 .

Table 2
Aircraft Characteristics and Capacities

	IL-76T and IL-76M	C-141B		IL-76T and IL-76M	C-141B
Dimensions			Cargo Compartment		
Length	46.6	51.3	Length (exclu- ding ramp)	19.7	27.7
Height	14.75	12.0	Height	3.5	2.77
Wing span	50.5	48.8	Width	3.45	3.12
Wing area (square meters)	329	300	Ramp Length	9.4	6.0
Wing sweep (degrees)	27	27	Ramp Width	3.4	3.1
			Ramp Slope (degrees)	10	15
Power Plant			Weight		
Manufacturer	Soloviyev	Pratt and Whitney	Maximum takeoff (kilograms)	170,000 ^d	155,600 ^b
Engine Model	D-30KP (four)	TF 33-P-7 (four)	No payload (kilograms)	IL-76T: 82,000 ^d IL-76M: 86,000 ^d	65,500
Thrust rating (kilograms)	12,000	9,530	Maximum payload (kilograms)	40,000 ^d	42,900 ^b
Specific fuel consumption at takeoff (kilogram/ kilogram/hour)	.5055	.56	Maximum fuel (kilograms)	84,500 ^d	69,600
Performance			Personnel Capacity		
Cruise speed (kilometers/hour)	750-800	750-785	Crew	5 to 7	4 (plus 4 alternate)
Cruise altitude (kilometers)	10-13	10-12.5	Troops	140e	209
Range with maximum payload (kilometers)	IL-76T 4,400 IL-76M 4,000 ^a	4,600 ^b	Paratroops	125	168
Take-off distance ^c	2,300	2,000 ^b	Litters	72	108

Note: Undefined measurements are in meters.

^dThe IL-76TD and MD variants have a maximum takeoff weight of 190,000 kilograms. Maximum fuel weight is estimated to be 90,500 kilograms and maximum payload at least 50,000 kilograms. Maximum landing weight may also have increased. The operating weight when empty is probably somewhat greater than that of the IL-76 and IL-76M. ^eCapacity is 225 people if the plane has a double-deck configuration.

^aThe IL-76TD and MD variants have roughly a 1,700-kilometer greater range.

bThis number is for a G-load factor of 2.25. At a 2.5 G-load factor the range would change to 5,100 kilometers and the take-off distance to 1,800 meters. Takeoff weight would decrease to 146,600 kilograms and payload to 33,700 kilograms. Calculated at sea level, with maximum weight, to clear a 15-meter height at end of runway.

25 X 1		

Soviet and US Production: Major Differences in Philosophy

The IL-76 production rates, while fairly representative of Soviet aircraft production, are dissimilar to the rates found in a profit-oriented market such as the US industry. Contrasting the IL-76 and its US lookalike, the C-141, reveals some of the major differences in production philosophy:

IL-76

- 470 built between 1974 and late 1985; average 39 per year.
- Overall number likely to increase by 65 percent as production continues into the 1990s.

C-141

- 285 built between 1963 and 1965; average 95 per vear.
- 270 of the original C-141s were modified between 1979 and 1982 to extend their role life.

The number of IL-76s built by the Soviets in the first nine years of production is similar to the number of C-141s built by the US in three years. The US manufacturers, responding to US Air Force procurement allowances for these three years, began a high-volume, mass production program. In contrast, the Soviets—working with long-term central planning cycles, quota systems, parts supply difficulties, and antiquated manufacturing machinery—have opted for a long and steady production

un.		25X1
	·	
		051/4
		25X1

Top Secret

25X1

25X1

25X1

25X1

25X1

25X1 25X1

The increasing output of IL-76s over the past decade can be represented graphically by means of a "learning curve." In a mass production program for complex items such as an aircraft, administrative, delivery, and assembly procedures should become more efficient over time, reducing the effort and cost of later units. This movement toward increased efficiency can be plotted and used to describe and predict production output at various points during a production program. The increase in output of IL-76s since 1974 shows such a trend towards increased efficiency and correlates with a 76-percent learning curve (that is, only 76 percent of the time is needed to produce the 200th plane as was needed to produce the 100th plane).


the increase in output since


the increase in output since that time is adequately explained as a function of the learning curve. A later section of this paper will return to these factors and the potential they have in helping predict future IL-76 output.

Figure 2 IL-76 Production, 1973-85

Rate of IL-76 Production

Cumulative IL-76 Production





25X1



25X1

Deployment

During the first two and a half years of production, all IL-76s (about 35 aircraft) were delivered to the Soviet military. Since then, allocations of newly produced IL-76s have gone to other customers as well as the military, and the allocation ratios have remained fairly constant throughout the production run. About 70 percent have gone to the military, 11 percent to Soviet civil aviation (Aeroflot), 12 percent have been exported, and 7 percent have been modified for special roles. Of those IL-76s modified for special roles, two variants—an AWACS and a refueling tanker—have recently been developed into production models, but only a few have been produced so far.

25X1

25X1

The IL-76 has been a reliable aircraft, and at least ninetyeight percent of those produced are still operational. 25X1

Military Aircraft

The primary customer for IL-76s has been Soviet Military Transport Aviation (Voyenno-Transportnaya Aviatsiya—VTA), the Soviet equivalent of the US Military Airlift Command (MAC). By late 1985, we estimate 330 military IL-76s had been

25X1

produced

25X1

The replacement of AN-12s with IL-76s has not been on a one-for-one basis. An AN-12 regiment, comprising 33 to 36 aircraft, is being replaced by a regiment of 28 IL-76s.4 The lift capability of an IL-

25X1

25X1

Top Secret

8

The Impact of IL-76s on Soviet Airborne Forces

The IL-76 brings capabilities to Soviet military transport service that are significantly greater than those of the AN-12. An individual IL-76 holds, roughly, twice as much cargo as the AN-12 and can carry it twice as far at a third higher speed. For the VTA, the principal user, the IL-76 offers many improvements over the AN-12. A regiment of IL-76s can carry about 560,000 kilograms (50 percent of its maximum payload) up to a distance of 6,500 kilometers in a single airlift. (The IL-76 TD and MD variants can travel over 7,500 kilometers with the same weight.) An AN-12 regiment is able to move only about 350,000 kilograms (50 percent of its maximum load) a distance of 3,300 kilometers. In an airborne role, compared to the AN-12, the IL-76


- · Carry three rather than two BMD armored personnel carriers.
- Carry 125 rather than 60 paratroopers.
- Carry its passengers in a pressurized cabin, rather than requiring individual oxygen supplies because of unpressurized cabins.

Concurrent with the upgrading of the VTA with IL-76s, there has been a modernization of the Soviet airborne forces. They are being equipped with larger numbers of new, air-transportable weapons and vehicles, which require the greater lift capability of the IL-76 regiments.

76 regiment, however, is roughly double that of an

AN-12 regiment.

The principal mission of the VTA (and thus of the IL-76) is to provide airlift support to the Soviet Airborne Forces. Additional missions include transport of nuclear weapons, logistic support for Soviet military forces, transport abroad of economic and military assistance cargoes, and occasional airlift assistance for Soviet civilian industries. IL-76s have participated in all major Soviet airlift exercises and operations since 1979. Of particular importance was the December 1979 airlift of Soviet airborne and ground forces into Afghanistan. About 70 IL-76s participated in this threeday operation.



, , , , , , , , , , , , , , , , , , ,											
								Top Se	ecret		25
•											20
								•			
ſ					7						
											25
						•					
					Export A	Aircraft					
						78 the So	oviets h	ave expo	orted 56	IL-76s.	
					Exports	include b	ooth the	military	y and civ	vil ver-	
						s of late 1	1985, fi	ve count	ries had	received	
					IL-76s:						
								~ .			_
					Takal	Libya	Iraq	Syria	Cuba	India	_
					Total Military	24 5	20 10 ^a	2	0	6	-
					Civil	19	10	2	2	0	
						aft is regist					-
						les to all					
1					ing ing	ics to aii	or these	Countri	cs are ce	Jiitiiiu-	-2
											;
X 1	Civil (Aerofle										
X 1	About 52 IL- il aviation (A	-76s have been of Aeroflot) since 1 duction has aver	976. Aero	flot's share							
	About 52 IL- il aviation (A of IL-76 prod	-76s have been of Aeroflot) since 1 duction has aver	976. Aero	flot's share							
X1 25X1	About 52 IL- il aviation (A of IL-76 prod	-76s have been of Aeroflot) since 1 duction has aver	976. Aero	flot's share							
	About 52 IL- il aviation (A of IL-76 prod	-76s have been of Aeroflot) since 1 duction has aver	976. Aero	flot's share							28
X1 25X1	About 52 IL- il aviation (A of IL-76 prod	-76s have been of Aeroflot) since 1 duction has aver	976. Aero	flot's share				Top S			



25X1

25X1

25X1

*		Top source	25 X 1
•		25X1	
25X1	Airborne Tanker.	transfer 40 metric tons of fuel and then return to base. We estimate the fuel transfer rate for this system to be at least 1,500 kilograms per minute per hose.7 IL-76 tankers will not be as difficult or time consuming to produce as the AWACS. Some extra steps will be required to install the pods and internal plumbing. These operations, however, should not be too difficult to implement on the existing assembly line; by 1987 we believe that six to eight IL-76 tankers may be produced each year.	25X1 -25X1 -25X1 -25X1
25X1			
25 X 1			
25 X 1 ,	By adding a fleet of IL-76 tankers, the Soviets will greatly enhance their ability to conduct missions of long distance or long duration. Two fighter-size aircraft can refuel simultaneously from the underwing pods. Larger aircraft will likely be refueled singly from the aft fuselage station. The IL-76 tanker appears to use the basic military version and, because of the advantages of higher gross weight and fuel load, will probably be produced with an IL-76MD airframe. Based upon this assumption, we believe the IL-76 tanker will probably have over 100 metric tons of fuel at takeoff. After flying a distance of 2,800 kilometers, it could		
	25X1	· ,	

Sanitized Copy Approved for Release 2009/11/09: CIA-RDP90T01298R000300250001-4

13



25X1

25X1

25X1

With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		Top Secret
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		<u>. </u>
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		
With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions		·
quire dedicated repair facilities to keep these aircraft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions	Maintenance	
craft in service. Inspections, maintenance, repairs, and replacement of parts and systems are handled through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions	With their growing fleet of IL-76s, the Soviets require dedicated repair facilities to keep these air-	
through regimented and predetermined schedules. A part is inspected and serviced at regular intervals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-level repair functions 25X1 25X1	craft in service. Inspections, maintenance, repairs,	
vals, but once it has reached its safety service lifetime, it is replaced automatically (usually at a time far before it would be replaced in the US system). Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lever repair functions 25X1 25X1	through regimented and predetermined schedules.	The Soviet civil version of the IL-76 undergoes d
Aging aircraft also will require structural repairs or major maintenance that cannot be performed at the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions	vals, but once it has reached its safety service life- time, it is replaced automatically (usually at a time	pot-level repair at the Moscow-Bykovo Repair
the deployment bases. Thus, depot-level repair and overhaul facilities are needed for the IL-76. Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions 25X1 25X1		
Most work at Moscow-Bykovo done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions 25X1 25X1	the deployment bases. Thus, depot-level repair	
done on intact airframes, and much of it is done the open. This, we believe, is typical of depot-lev repair functions 25X1 25X1	and overhaul facilities are needed for the IL-76.	
repair functions 25X1 25X1		done on intact airframes, and much of it is done
		
		
	25V1	OFW4
15 Top Secret		Z3X1

Sanitized Copy Approved for Release 2009/11/09: CIA-RDP90T01298R000300250001-4

Assessment of Future Production
In order to fulfill estimated user requirements, the Soviets will have to keep the IL-76 in production until the early 1990s. By late 1985 some 470 IL-76

Sanitized Copy Approved for Release 2009/11/09 : CIA-RDP90T01298R000300250001-4

Top Secret

Top Secret

Sanitized Copy Approved for Release 2009/11/09: CIA-RDP90T01298R000300250001-4

16



18

